

DISPLAY MAINTENANCE

1. General remarks

- a. Remove the protective film and self-adhesive labels up to 3 weeks after the installation of the roller shutters or gates.
- b. Do not use abrasive cleaning agents.

2. Glass cleaning – general instructions

- a. Use a clean cloth soaked in water.
- b. Use branded glass cleaning solutions and follow all instructions.
- c. Remove cleaning solutions immediately with a clean, soft and dry cloth.
- d. Use a 50:50 alcohol-water or ammonia-water solution, then rinse with warm water.
- e. Wipe the glass dry with a clean, soft cloth or a suede or cellulose sponge.

3. Precautions

- a. Avoid abrasive or highly alkaline cleaning agents.
- b. Do not use petroleum products, i.e. petrol, diesel fuel or lighter liquids.
- c. Hydrofluoric and phosphoric acids have a corrosive effect on the glass surface and should not be used.
- d. Protect the surface of the glass from sprayed drops or leaks of acids and cleaning agents used to clean metal frames, bricks or masonry, as well as from weld spatters.
- e. The edges of laminated glass and glazed units must be protected from contact with all cleaning solutions and other materials.
- f. Do not use hard brushes, razor blades or other objects that could scratch the glass.
- g. Immediately remove all construction materials from the glass, i.e. concrete, fire retardants, paints.
- h. Each time clean a small area of glass with a clean cloth and frequently check it for damage.